




APPROVED: _____
 DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-	7560	RELEASED	2/22/07	
A	7560	REVISED SPEC.	2/15/11	



PIN Ø X
 (SEE CHART)

PART NO.	CENTER PIN DIA.
ADC-008A-1	.078 [2.00]
ADC-008A-5	.092 [2.35]
ADC-008A-2	.098 [2.50]



B SPECIFICATIONS:

Material:
 Insulator: PBT, Glass reinforced, rated UL 94V-0
 Insulator color: Black
 Center Pin: Brass, tin plated
 Contacts: Brass
 Spring: Stainless Steel, tin plated
 Plating:
 Tin over Copper underplate on tails
 Electrical:
 Operating voltage: 20 VDC max.
 Current rating: 2.5 Amp max.
 Contact resistance: 50 mohms max. initial
 Insulation resistance: 100 Mohms min.
 Dielectric withstanding voltage: 500 VAC for 1 minute
 Temperature Rating:
 Operating temperature: -20°C to +70°C
 Environmental:
 Lead free, RoHS compliant.
 Recommended soldering temp: 235°C. for 5 sec.

A

ADAM TECH
 909 Rahway Avenue, Union, NJ 07083
 Phone: 908-687-5000 Fax: 908-687-5710

DC POWER JACK

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM]	
TOLERANCES: EXCEPT AS NOTED	
INCHES	HOLDS
.X ± .10	± .10
.XX ± .020	± .015
.XXX ± .015	± .010
APPROVALS	DATE
DRAWN	BW
CHECKED	
APPROVED	

SIZE	PART NO.	REV.
X	ADC-008A-X	A
REF:	S00002C	SCALE: NTS
SHEET	1 OF 1	

