

6 5 4 3 2 1

APPROVED: _____
 DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-		RELEASED	3/1/16	

RECOMMENDED PCB LAYOUT

SPECIFICATIONS:

Material:
 Insulator: Hi-temp thermoplastic, rated UL 94V-0
 Insulator color: Black
 Contacts: Copper Alloy
 Plating:
 Tin over Copper underplate overall.
 Electrical:
 Operating voltage: 200 VAC
 Current rating: 0.5 Amps
 Contact resistance: 20 mohms max. initial
 Insulation resistance: 1,000 Mohms min
 Environmental:
 Lead free, RoHS compliant

Positions: 6 thru 36

A = .031 [0.80] x No. of Space

B = .031 [0.80] x No. of Space + .071 [1.80]

C = .031 [0.80] x No. of Space + .102 [2.60]

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM] TOLERANCES: EXCEPT AS NOTED		ADAM TECH 909 Rahway Avenue, Union, NJ 07083 Phone: 908-687-5000 Fax: 908-687-5710	
INCHES HOLES .X ± .10 Ø.X ± .10 .XX ± .020 Ø.XX ± .015 .XXX ± .015 Ø.XXX ± .010			
APPROVALS		TITLE	
DRAWN	AY	.031 [0.80] BOARD TO BOARD PLUG, SMT TYPE, .189 [4.80] HEIGHT	
CHECKED	MY	DATE	3/1/16
APPROVED		DATE	3/1/16
SIZE	PART NO.	REV.	
X	BB8-PEB-XX-T-4.80-T/R	-	
REF:	S00128T	SCALE:	NTS
		SHEET 1 OF 1	

6 5 4 3 2 1