

6 5 4 3 2 1

APPROVED: _____
 DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-		RELEASED	3/1/16	

D

C

RECOMMENDED PCB LAYOUT

B

SPECIFICATIONS:

Material:
 Insulator: Hi-temp thermoplastic, rated UL 94V-0
 Insulator color: Black
 Contacts: Copper Alloy
 Hold down: Copper Alloy
 Plating:
 Tin over Copper underplate overall.
 Electrical:
 Operating voltage: 200 VAC max
 Current rating: 0.5 Amps max
 Contact resistance: 20 mohms max. initial
 Insulation resistance: 1000 Mohms min
 Environmental:
 Lead free, RoHS compliant

PACKAGED ON TAPE & REEL

Positions: 6 thru 36

A = .031 [0.80] x (No. of Contacts per row - 1)

B = .031 [0.80] x (No. of Contacts per row - 1) + .094 [2.40]

C = .031 [0.80] x (No. of Contacts per row - 1) + .071 [1.80]

UNLESS OTHERWISE SPECIFIED
 ALL DIMENSIONS ARE INCHES [MM]
 TOLERANCES: EXCEPT AS NOTED

INCHES		HOLES	
.X	± .10	Ø.X	± .10
.XX	± .020	Ø.XX	± .015
.XXX	± .015	Ø.XXX	± .010

ADAM TECH

909 Rahway Avenue, Union, NJ 07083
 Phone: 908-687-5000 Fax: 908-687-5710

TITLE: .031 [0.80] BOARD TO BOARD SOCKET, SMT TYPE
 3.30MM HEIGHT, W/WMLAR

APPROVALS		DATE
DRAWN	AY	3/1/16
CHECKED	MY	3/1/16
APPROVED		

SIZE	PART NO.	REV.
X	BB8-SEB-XX-T-3.30-KT-T/R	-
REF: S00128T	SCALE: NTS	SHEET 1 OF 1

6 5 4 3 2 1