



SPECIFICATIONS:

Material: Hi-temp thermoplastic, rated UL 94V-0
Housing: Copper Alloy
Contact: Copper Alloy
Shell: Copper Alloy, nickel plated
Plating: 15u" Gold over Nickel underplate on contact area
Electrical: Tin plating on Solder Tail
Operating voltage: 40 VAC
Current rating: 0.5 Amps min
Conduct Resistance: 50 ohms max
Insulation Resistance: 100M ohms min.
Withstanding Voltage: 500V AC for 1 minute
Temperature Rating: Operating temperature: -20°C to +85°C
Environmental: Lead free, RoHS compliant.

ADAM TECH

909 Rahway Avenue, Union, NJ 07083
 Phone: 908-687-5000 Fax: 908-687-5710

UNLESS OTHERWISE SPECIFIED
 ALL DIMENSIONS ARE IN INCHES [MM]
 TOLERANCES: EXCEPT AS NOTED

INCHES	HOLES
.X ± .10	± .10
.XX ± .020	± .015
.XXX ± .015	± .010

APPROVALS	DATE
DRAWN AY	5/29/14
CHECKED LL	5/29/14
APPROVED	

SIZE	PART NO.	REV.
X	DPC-F-S-RA-TSMT-NP-MF-15-KT-1/R	-