

6 5 4 3 2 1

APPROVED: _____
DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-		RELEASED	11/24/14	

Top view showing dimensions: $.197 [5.00]$ and B .

Side view showing dimensions: $.197 [5.00]$ and A .

SECTION A-A showing dimensions: $.496 [12.60]$, $1.024 [26.00]$, and $.327 [8.30]$.

SPECIFICATIONS:
 Material:
 Insulator: PA66, rated UL 94V-0
 Insulator color: Black
 Screws: M3, Steel, Zinc plated
 Clamp: Phosphor Bronze, Nickel plated
 Cage: Brass, Nickel plated
 Electrical:
 Voltage rated: 300 VAC
 Current rating: 15 Amps
 Contact resistance: 20 mohms max
 Insulation resistance: 500 Mohms min @ 500 VDC
 Dielectric withstanding voltage: 2,000 VAC for 1 minute
 Wire range: 28-14 AWG
 Torque: 0.5Nm, 4.5lb-in
 Wire strip length: 7-8mm
 Temperature Rating:
 Operating temperature: -40°C to +105°C
 Environmental:
 Lead free, RoHS compliant.

Only This Notch on 2P

SECTION A-A

Positions: 02 thru 24
 $A = .197 [5.00] \times \text{No. of Positions}$
 $B = .197 [5.00] \times \text{No. of Spaces}$

UNLESS OTHERWISE SPECIFIED
 ALL DIMENSIONS ARE INCHES [MM]
 TOLERANCES: EXCEPT AS NOTED

INCHES		HOLES	
.X	$\pm .10$	$\varnothing X$	$\pm .10$
.XX	$\pm .020$	$\varnothing XX$	$\pm .015$
.XXX	$\pm .015$	$\varnothing XXX$	$\pm .010$

ADAM TECH

909 Rahway Avenue, Union, NJ 07083
 Phone: 908-687-5000 Fax: 908-687-5710

TITLE: EURO BLOCK, .197 [5.00] PITCH, BLACK WITH FLANGE

APPROVALS		DATE
DRAWN	AY	4/29/16
CHECKED	IC	4/29/16
APPROVED		

SIZE X	PART NO. EB9A-XX-C-E-BK	REV. -
REF: S00067C	SCALE: NTS	SHEET 1 OF 1

6 5 4 3 2 1