

6 5 4 3 2 1

APPROVED: \_\_\_\_\_  
 DATE: \_\_\_\_\_ TITLE: \_\_\_\_\_

Rev	AWO #	Description	Date	Appr
-		RELEASED	12/30/14	

**SPECIFICATIONS:**

Material:  
 Insulator: PA66, rated UL 94V-0  
 Insulator color: Green  
 Screws: M3, Steel, Zinc plated  
 Cage: Brass, Nickel plated  
 Clamp: Phosphor Bronze, Nickel plated  
 Electrical:  
 Voltage rated: 300 VAC  
 Current rating: 15 Amps  
 Contact resistance: 20 mohms max  
 Insulation resistance: 500 Mohms min @ 500 VDC  
 Dielectric withstanding voltage: 2,000 VAC for 1 minute  
 Wire range: 28-14 AWG, 2.5mm<sup>2</sup>  
 Torque (lb-in): 0.5Nm (4.5Lb.in)  
 Wire strip length: 7-8mm  
 Temperature Rating:  
 Operating temperature: -40°C to +105°C  
 Environmental:  
 Lead free, RoHS compliant.

Positions: 2 thru 24  
 A= .300 [7.62] x No. of Positions - .079 [2.00]  
 B= .300 [7.62] x No. of Spaces

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM] TOLERANCES: EXCEPT AS NOTED		<h2 style="text-align: center;">ADAM TECH</h2> <p style="text-align: center;">909 Rahway Avenue, Union, NJ 07083                  Phone: 908-687-5000 Fax: 908-687-5710</p>																	
<table border="1"> <tr> <th colspan="2">INCHES</th> <th colspan="2">HOLES</th> </tr> <tr> <td>.X</td> <td>± .10</td> <td>Ø.X</td> <td>± .10</td> </tr> <tr> <td>.XX</td> <td>± .020</td> <td>Ø.XX</td> <td>± .015</td> </tr> <tr> <td>.XXX</td> <td>± .015</td> <td>Ø.XXX</td> <td>± .010</td> </tr> </table>				INCHES		HOLES		.X	± .10	Ø.X	± .10	.XX	± .020	Ø.XX	± .015	.XXX	± .015	Ø.XXX	± .010
INCHES		HOLES																	
.X	± .10	Ø.X	± .10																
.XX	± .020	Ø.XX	± .015																
.XXX	± .015	Ø.XXX	± .010																
APPROVALS		DATE																	
DRAWN	AY	12/30/14																	
CHECKED	WY	12/30/14																	
APPROVED																			
SIZE	PART NO.	REV.																	
X	EB9A-XX-G	-																	
REF:	S00067C	SCALE:	NTS																
		SHEET 1 OF 1																	

6 5 4 3 2 1