

6 5 4 3 2 1

APPROVED: \_\_\_\_\_  
 DATE: \_\_\_\_\_ TITLE: \_\_\_\_\_

Rev	AWO #	Description	Date	Appr
-		RELEASED	4/29/15	

D  
C  
B  
A

D  
C  
B  
A

**SPECIFICATIONS:**

Material:  
 Insulator: PA66, rated UL 94V-0  
 Insulator color: Green  
 Screws: M3, Steel, Zinc plated  
 Cage: Brass, Nickel plated  
 Clamp: Phosphor Bronze, Nickel plated  
 Electrical:  
 Voltage rated: 300 VAC  
 Current rating: 15 Amps  
 Contact resistance: 20 mohms max  
 Insulation resistance: 500 Mohms min @ 500 VDC  
 Dielectric withstanding voltage: 2,000 VAC for 1 minute  
 Wire range: 28-14 AWG, 1.5mm<sup>2</sup>  
 Torque (lb-in): 0.5Nm (4.5Lb.in)  
 Wire strip length: 7-8mm  
 Temperature Rating:  
 Operating temperature: -40°C to +105°C  
 Environmental:  
 Lead free, RoHS compliant.

Positions: 2 thru 24  
 A= .295 [7.50] x No. of Positions - .079 [2.00]  
 B= .295 [7.50] x No. of Spaces

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM] TOLERANCES: EXCEPT AS NOTED		<b>ADAM TECH</b> 909 Rahway Avenue, Union, NJ 07083 Phone: 908-687-5000 Fax: 908-687-5710	
INCHES HOLES			
.X ± .10	∅X ± .10	TITLE EURO BLOCK, .295 [7.50] PITCH HOOKS ON ENTRY SIDE	
.XX ± .020	∅XX ± .015		
.XXX ± .015	∅XXX ± .010		
APPROVALS		DATE	
DRAWN AY		4/29/15	
CHECKED KW		4/29/15	
APPROVED		SIZE X	PART NO. EB9A-XX-M
		REF: S00067C	SCALE: NTS SHEET 1 OF 1

6 5 4 3 2 1