



SPECIFICATIONS:

Material:
 Insulator: Hi-Temp Thermoplastic, rated UL 94V-0
 Insulator color: Black
 Contacts: Copper Alloy
 Plating:
 15u" Gold over Nickel underplate on contact area,
 Matte Tin over Nickel underplate on solder tails
 Electrical:
 Current rating: 0.5 Amp max
 Insulation resistance: 100 Mohms min (Unmate) / 10 Mohms min (Mate)
 Dielectric withstanding voltage: 500 VAC (Unmate) / 300 VAC (Mate)
 Temperature Rating:
 Operating temperature: -25°C to +85°C
 Environmental:
 Lead free, RoHS compliant



6	5	4	3	2	1
Rev	AWO #	Description		Date	Appr
-		RELEASED		8/5/16	

UNLESS OTHERWISE SPECIFIED
 ALL DIMENSIONS ARE INCHES [MM]
 TOLERANCES: EXCEPT AS NOTED

.X	± .10	∅X	± .10
.XX	± .020	∅.XX	± .015
.XXX	± .015	∅.XXX	± .010

APPROVALS		DATE
DRAWN	HR	8/5/16
CHECKED	CH	8/5/16
APPROVED		

ADAM TECH
 909 Rahway Avenue, Union, NJ 07083
 Phone: 908-687-5000 Fax: 908-687-5710

TITLE: DUAL HDMI CONNECTOR, MOUNTING FLANG

SIZE	PART NO.	REV.
X	HDMI-D-RA-1A-MF-15	-

REF: S00027T SCALE: NTS SHEET 1 OF 1