Rev	AWO #	Description	Date	Appr
-		RELEASED	4/22/08	

APPROVED: _____

DATE: _____ TITLE: _____







PCB LAYOUT
(BOTTOM VIEW)

ROW A COLOR = WHITE (TOP PORT)
ROW B COLOR = RED (BOTTOM PORT)

CIRCUIT TYPE 4

RCA–10–4



SPECIFICATIONS:
Material:
Insulator: PBT, Glass reinforced, rated UL 94V–0
Insulator colors: Red, Black, Yellow, White
Bushing: Brass, Gold Plated
Contacts: Brass
Contact Plating:
Gold Flash over Nickel underplate
Electrical:
Operating voltage: 12 VDC max.
Current rating: 1 Amp max.
Contact resistance: 30 mohms max. initial
Insulation resistance: 100 Mohms min.
Dielectric withstanding voltage: 500 VAC for 1 minute
Temperature Rating:
Operating temperature: –25°C to +85°C
Environmental:
Lead free, RoHS compliant.
Recommended soldering temp: 235°C for 5 sec.

RoHS COMPLIANT

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE INCHES [MM]
TOLERANCES: EXCEPT AS NOTED

INCHES		HOLES	
.X	± .10	Ø.X	±.10
.XX	± .020	Ø.XX	±.015
.XXX	± .015	Ø.XXX	±.010

APPROVALS		DATE
DRAWN	SS	4/22/08
CHECKED		
APPROVED		

ADAM TECH
909 Rahway Avenue, Union, NJ 07083
Phone: 908-687-5000 Fax: 908-687-5710

TITLE: RCA JACK, 4 PORTS, 2 X 2, TOP/BOTTOM GOLD PLATED

SIZE	PART NO.	REV.
X	RCA-10-4-W/R-G	-

REF: | SCALE: NTS | SHEET 1 OF 1