



SPECIFICATIONS:

Material:

Insulator: ABS, Colors: White

Cover: ABS, Colors: Black

Insert Ring: PBT, Glass reinforced, rated UL 94V-0

Insert Ring colors: Red, White

Barrel: Brass, Nickel plated

Contacts: Brass

Plating:

Tin over Copper underplate overall

Electrical:

Current rating: 2A Max. @12V DC

1A Max. @100V AC

Contact resistance: 30 mohms max. initial

Insulation resistance: 100 Mohms min.

Dielectric withstanding voltage: 500 VAC for 1 minute

Mechanical:

Durability: 4,000 Cycles

Environmental:

Lead free, RoHS compliant.



UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM] TOLERANCES: EXCEPT AS NOTED INCHES HOLES		
.X ± .10	$\phi$ .X ± .10	
.XX ± .020	$\phi$ .XX ± .015	
.XXX ± .015	$\phi$ .XXX ± .010	
APPROVALS		DATE
DRAWN	AY	11/12/15
CHECKED	YC	11/12/15
APPROVED		

<b>ADAM TECH</b>		
909 Rahway Avenue, Union, NJ 07083		
Phone: 908-687-5000 Fax: 908-687-5710		
TITLE		
RCA JACK, 4 PORTS, 2 X 2		
SIZE	PART NO.	REV.
X	RCA-10A-4-R/R/W/W	-
REF:	S00095T	SCALE: NTS
		SHEET 1 OF 1