



NO	Description	Qty	Material	Finish
9	RING	1	BRASS	Nickel
8	PIN	1	BRASS	GOLD
7	WASHER	1	BRASS	NICKEL
6	INSULATOR	1	TEFLON	NONE
5	GASKET	1	RUBBER	RED
4	WASHER	1	BRASS	NICKEL
3	NUT	1	BRASS	NICKEL
2	BODY	1	BRASS	Nickel
1	BODY	1	BRASS	Nickel

ADAM TECH

909 Rahway Avenue, Union, NJ 07083
 Phone: 908-687-5000 Fax: 908-687-5710

TITLE: **BNC FEMALE BULKHEAD CRIMP FOR RG179JU, 75 OHM**

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE MM [INCHES] TOLERANCES: EXCEPT AS NOTED	
.X	± .10
.XX	± .020
.XXX	± .015
.XXX	± .010
ØX	± .10
ØXX	± .015
ØXXX	± .010
APPROVALS	DATE
DRAWN	SLS
CHECKED	
APPROVED	

SIZE	PART NO.	REV.
X	RF1-04-T-03-75	
REF:	SCALE: NTS	SHEET 1 OF 1

CONNECTOR SPECIFICATIONS:

ELECTRICAL:
 Operating Voltage: 500 VAC max.
 Impedance: 75 ohms; Frequency Range: 0-4 GHz
 Contact Resistance: Inner: 6 - Outer: 3 mohms
 Insulation Resistance: 5000 Mohms (min.) @ 1500 VDC
 between adjacent contacts (75°F and 50 % R.H.)

TEMPERATURE RATING:

Operating Temperature: -55°C to +85°C
 Environmental:
 Lead free, RoHS compliant.

